

## CLAIMS

While the embodiments of the invention have been disclosed, certain modifications may be made by those skilled in the art to modify the invention without departing from the spirit of the invention. The inventor claims:

1. A device to be attached to the front of a tractor blade which comprises a base member, a top rod, end plates, angle clips, removable securing rod, cotter pins and a means of attachment;  
  
said end plates are connected to the outside edge of the base plate and extend vertically from the point of attachment the approximate height of a tractor blade;  
  
said top rod connects the topmost point of the end plates;  
  
said means of attachment allows the device to be secured in place by resting the top rod over the top of the tractor blade and the removable securing rod against the back surface of the tractor blade.
2. The angle clips as described in claim 1, wherein they are attached to the interior of the side of the end plates.
3. The angle clips as described in claim 2, wherein they are welded to the interior surface of the respective end plates.

4. The angle clips as described in claim 2, wherein there are two angle clips per end plate.
5. The top rod as described in claim 1, wherein it is attached to the top surface of the end plates.
6. The end plates as described in claim 1, wherein they are perpendicular to the bottom plate on both sides.
7. The means of attachment, as described in claim 1, wherein cotter pins are used.
8. A device to be attached to the front of a tractor blade which comprises a base member, a top rod, end plates, angle clips, pins and a means of attachment;  
  
said end plates are connected to the outside edge of the base plate and extend vertically from the point of attachment the approximate height of a tractor blade;  
  
said top rod connects the topmost point of the end plates;  
  
said means of attachment allows the device to be secured in place by resting the top rod over the top of the tractor blade and the means of attachment against the back surface of the tractor blade.
9. The angle clips as described in claim 1, wherein they are attached to the interior of the side of the end plates.

10. The angle clips as described in claim 8, wherein they are welded to the interior surface of the respective end plates.
11. The angle clips as described in claim 2, wherein there are two angle clips per end plate.
12. The top rod as described in claim 1, wherein the top rod is attached to the top surface of the end plates.
13. The end plates as described in claim 1, wherein they are perpendicular to the bottom plate on both sides.
14. The means of attachment, as described in claim 8, wherein pins are used.
15. The means of attachment as described in claim 8, wherein a nut and bolt is used.